



FREE Instruments!

TPI Fall Savings 2017

BUY THIS:

**TPI 709P
\$549.⁹⁵**



GET THIS:

**TPI 709P
& FREE
725L
(\$620.⁰⁰ Value)**



Get a **FREE TPI 725L Combustible Gas Leak Detector** with the Purchase of TPI 717P Combustion Efficiency Analyzer!

TPI 709P

Includes a built-in high-resolution (0.001 inH₂O) differential manometer capable of accurately measuring pressure and draft.

- CO accuracy +/-5 ppm below 100 ppm for IAQ testing.
- O₂, excess air, CO, CO₂, temperature, pressure, efficiency.
- Fast purge and easy fuel selection during start up
- Built in high-resolution (0.001 inH₂O) differential manometer
- Measures CO, O₂, pressure and temperature

For a Limited Time, purchase the TPI 709P for \$549.95 and receive a TPI 725L for FREE.

Ask Your Dealer for Information, or call 1-800-368-5719 and ask for Pete.



TPI 725L

Combustible Gas Leak Detector

Find the source of combustible gas leaks in valves, pipes, and fittings.

40 PPM methane sensitivity, detects combustible gases including: Methane, Butane,

Propane, Gasoline, Diesel and Kerosene.

Tick rate can be nullified to eliminate background gas concentration and pinpoint the leak source.

40ppm methane sensitivity. Trace natural gas lines and fittings for leaks. Check propane tanks, fittings, lines, and heaters for leaks. Test confined spaces for gas build-up

\$69.95 Suggested List Price, FREE with this OFFER!

Test the TPI Advantage & Save!



Value Driven, Professional & Extensive Product Offerings

TLK3 Trouble Shooting Test Lead Kit


FITS ALL MAJOR BRANDS OF METERS



- A057 back probes ideal to trouble shoot ECMs, Molex connectors or Molex type connector
- A080 UL listed silicone test leads
- A052 modular male banana plug to screw tip test leads like the A080
- A150 Screw on alligator clips with boots
- 3-year limited warranty

\$24.95

133 Full Size DMM



- Large easy to read display
- 0.5% basic DCV accuracy
- Measure up to: 750 ACV, 1,000 DCV, 20 MOHM, 10 A AC/DC
- Data hold
- Cat III 600 V; cULus

\$56.95

183a True RMS DMM



- Separate fuse and battery compartment, built in low pass filter, duty cycle, frequency, capacitance and temperature
- AC/DC volts & amps, resistance, audible continuity, diode test and data hold
- CAT III 600 V; cULus
- Optional A108 PC interface

\$159.95

270 Clamp-on Meter



- Slim jaw and body design for use in crowded electrical panels
- Measure motor in-rush and run current; 400 A AC
- Measure temperature differential with REL mode (direct input k-type thermocouple)
- Non-contact voltage, ACV, DCV (including millivolts), DC microamps, Capacitance, Frequency, Min/Max/Record and peak hold
- CAT III 600 V; cULus

\$129.95

315C Pocket Digital Thermometer



- Tapered stem (3.1 mm diameter) to fit into a Pete's Plug
- IP67 Waterproof and rugged
- Magnet perfect for air duct applications
- Auto field calibration to +/- 2°F in ice water in less than 10 seconds

\$18.95

343C2 Dual Input Thermometer



- Auto field calibration to a system accuracy (tester + probe) of +/- 1°F (30 to 120 °F) in less than 10 seconds in ice water
- Measure ambient or duct temperatures; plus rise and differential
- -58 to 2,462 °F tester range; limited by K-type thermocouple probe selected
- 343C2 includes: 342, GK13M, A304 and A340

\$79.95

343C3 \$129.95: 343C2 plus two CK21M

575C1 Combo Vane & Hot Wire

- Combo vane (air balancing) and hot wire (ducts) in one unit
- 39 inch cable length and hot wire telescoping extension for use inside air ducts



- Measure air velocity and temperature simultaneously
- Vane air flow: 0.4 to 25 m/s; hot wire air flow 0.2 to 20 m/s

\$249.95

621C3 Dual Input Differential Manometer

- Everything to hook up and use your 621: "T" fittings, barb fittings, silicone tubing, static tips and adapter tubing
- 0.001 inches H2O resolution less than 40 inches H2O



- Temperature compensated
- Over range protection to 15 PSI
- Wide range +/- 120 inches H2O; seven units of measure

\$259.95

381a Combo IR & Contact Thermometer



- Combination IR or contact (k-type) thermometer
- Temperature compensated
- Repeatable readings
- Free GK11M to measure air & duct temperature (\$14.95 value)
- Single button, last reading hold function
- -4 to 572 °F (non-contact) & -148 to 2,192 °F (contact) range, °C/°F selectable

\$74.95

725L Combustible Gas Leak Detector

- 40-ppm sensitivity
- Pocket sized
- Visual and audible leak indication
- 7.5 inch neck



\$69.95

775 Combo CO/Combustible Gas

- Combo ambient CO and combustible leak detector
- Up to 2,000 ppm CO with 1 ppm resolution; accuracy +/- 5 ppm or 5% whichever is greater
- Combustible leak: 50 ppm sensitivity with range of 50 to 50,000 ppm; +/- 10% accuracy
- Visual and audible leak detection (adjustable tic rate) with 16-inch gooseneck



\$374.95

709A740 Combustion Analyzer with Printer

- Lowest cost of ownership (initial price plus service)
- CO accuracy +/- 5 ppm below 100 ppm for ambient CO testing



- Protected against oversaturation with 10,000 ppm CO sensor
- Measure CO, O2, temperature and pressure calculate efficiency, CO2, excess air and CO air free
- A740 IR printer

\$674.95

FB-HVAC-0715 copyright 2017 Test Products Intl

Test Products International, Inc.
503-520-9197 Fax: 503-520-1225
e-mail: info@tpi-thevalueleader.com

www.testproductsintl.com

Test the TPI Advantage