



FREE Instruments!

TPI Fall Savings 2017



Combustion Efficiency Analyzer

TPI 716P

- CO accuracy +/-5 ppm below 100 ppm for IAQ testing.
- O₂, excess air, CO, CO₂, temperature, pressure, efficiency.
- 8-line graphical backlit display: more measurements at a glance.
- Upgradeable to NOX.
- Combustible leak probe (100 ppm) to check gas fittings.
- Optional Bluetooth available.

**Order
716P for \$1,195.00
to get your Free 270;
A \$129.95 Value**

Clamp Meter

TPI 270

- Up to 400 AC amps with 0.01 resolution
- Measure motor in-rush and run current
- Measure temperature differential
- Frequency, Min/Max/Record, Data Hold and Peak Hold
- Measure up to 40,000 Microfarads to test run and start capacitors
- NCV function detects down to 24V; ideal for testing thermostats
- Hi Voltage Indicator (>30V AC/DC)
- DCµA measurement (0.01µA resolution)



Ask Your Dealer for Information, or call 1-800-368-5719 and ask for Pete.

Test the TPI Advantage & Save!



Value Driven, Professional & Extensive Product Offerings

TLK3 Trouble Shooting Test Lead Kit


FITS ALL MAJOR BRANDS OF METERS



- A057 back probes ideal to trouble shoot ECMs, Molex connectors or Molex type connector
- A080 UL listed silicone test leads
- A052 modular male banana plug to screw tip test leads like the A080
- A150 Screw on alligator clips with boots
- 3-year limited warranty

\$24.95

133 Full Size DMM



- Large easy to read display
- 0.5% basic DCV accuracy
- Measure up to: 750 ACV, 1,000 DCV, 20 MOHM, 10 A AC/DC
- Data hold
- Cat III 600 V; cULus

\$56.95

183a True RMS DMM



- Separate fuse and battery compartment, built in low pass filter, duty cycle, frequency, capacitance and temperature
- AC/DC volts & amps, resistance, audible continuity, diode test and data hold
- CAT III 600 V; cULus
- Optional A108 PC interface

\$159.95

270 Clamp-on Meter



- Slim jaw and body design for use in crowded electrical panels
- Measure motor in-rush and run current; 400 A AC
- Measure temperature differential with REL mode (direct input k-type thermocouple)
- Non-contact voltage, ACV, DCV (including millivolts), DC microamps, Capacitance, Frequency, Min/Max/Record and peak hold
- CAT III 600 V; cULus

\$129.95

315C Pocket Digital Thermometer



- Tapered stem (3.1 mm diameter) to fit into a Pete's Plug
- IP67 Waterproof and rugged
- Magnet perfect for air duct applications
- Auto field calibration to +/- 2°F in ice water in less than 10 seconds

\$18.95

343C2 Dual Input Thermometer



- Auto field calibration to a system accuracy (tester + probe) of +/- 1°F (30 to 120 °F) in less than 10 seconds in ice water
- Measure ambient or duct temperatures; plus rise and differential
- -58 to 2,462 °F tester range; limited by K-type thermocouple probe selected
- 343C2 includes: 342, GK13M, A304 and A340

\$79.95

343C3 \$129.95; 343C2 plus two CK21M

575C1 Combo Vane & Hot Wire

- Combo vane (air balancing) and hot wire (ducts) in one unit
- 39 inch cable length and hot wire telescoping extension for use inside air ducts



- Measure air velocity and temperature simultaneously
- Vane air flow: 0.4 to 25 m/s; hot wire air flow 0.2 to 20 m/s

\$249.95

621C3 Dual Input Differential Manometer

- Everything to hook up and use your 621: "T" fittings, barb fittings, silicone tubing, static tips and adapter tubing
- 0.001 inches H2O resolution less than 40 inches H2O



- Temperature compensated
- Over range protection to 15 PSI
- Wide range +/- 120 inches H2O; seven units of measure

\$259.95

381a Combo IR & Contact Thermometer



- Combination IR or contact (k-type) thermometer
- Temperature compensated
- Repeatable readings
- Free GK11M to measure air & duct temperature (\$14.95 value)
- Single button, last reading hold function
- -4 to 572 °F (non-contact) & -148 to 2,192 °F (contact) range, °C/°F selectable

\$74.95

725L Combustible Gas Leak Detector

- 40-ppm sensitivity
- Pocket sized
- Visual and audible leak indication
- 7.5 inch neck



\$69.95

775 Combo CO/Combustible Gas



- Combo ambient CO and combustible leak detector
- Up to 2,000 ppm CO with 1 ppm resolution; accuracy +/- 5 ppm or 5% whichever is greater
- Combustible leak: 50 ppm sensitivity with range of 50 to 50,000 ppm; +/- 10% accuracy
- Visual and audible leak detection (adjustable tic rate) with 16-inch gooseneck

\$374.95

709A740 Combustion Analyzer with Printer

- Lowest cost of ownership (initial price plus service)
- CO accuracy +/- 5 ppm below 100 ppm for ambient CO testing



- Protected against oversaturation with 10,000 ppm CO sensor
- Measure CO, O2, temperature and pressure calculate efficiency, CO2, excess air and CO air free
- A740 IR printer

\$674.95

FB-HVAC-0715 copyright 2017 Test Products Intl